



# The Beneteau 54

## Standard Equipment and Options



Three cabin



Four cabin

LOA	.54'9"
Hull Length	.53'4"
LWL	.49'3"
Beam	.16'1"
Displacement	.32,838 lbs (approx)
Sail Area	.1,656 sq ft
Draft	(standard) 7'7" . . . (optional) 5'11"
Ballast (standard)	.9,998 lbs
Ballast (optional)	.11,001 lbs
Fuel capacity	.125 gal
Water	.256 gal
Auxiliary	.110 hp
Hull Design:	Berret-Racoupeau
Interior Design:	Nauta Design

Rig Dimensions: Mast	. . . . . Classic
I	. . . . . .64'
J	. . . . . .21'3"
P	. . . . . .62'4"
E	. . . . . .20'10"

### CONSTRUCTION

Hull constructed of hand-laid solid GRP bonded to a structural grid/hull liner of directional fiberglass/GRP for a strong, stiff, light composite. Vinylester hull barrier coat to resist osmotic blistering and zone-specific stitchmat laminates for specific increased strength optimization.

Deck constructed of Cored GRP sandwich construction for stiffness, thermal and acoustic insulation and lighter weight. Solid fiberglass reinforcements in high load areas. Integral unidirectional GRP deck beams for added strength. Main bulkheads bonded 360° to the hull and deck for rigid torsional and compression strength.

### DECK EQUIPMENT

#### RIGGING

Fractional 9/10 anodized aluminum deck stepped mast with double aft-swept spreaders  
Anodized aluminum boom  
Standing rigging, stainless steel  
Rigid boom vang led to cockpit  
Genoa furling system with drum on the deck  
Adjustable mainsheet traveler  
Genoa sheet tracks with adjustable lead cars  
Majority of running rigging led to cockpit  
Running rigging: Main halyard, genoa halyard w/jammer and cleat on mast, boom topping lift with cleat on mast, mainsail outhaul, (2) genoa sheets, (2) reefs  
(1) Line stoppers  
(6) Fairleads

#### WINCHES

(2) Self-tailing Genoa sheet winches, Harken H70.2 STC  
(2) Self tailing rigging winches, Harken H44.2 STC  
(2) Winch handles  
(2) Winch handle pockets

#### SAILS

Furling 135% Genoa with UV protective strip  
Full battened mainsail with roller mast track cars  
Lazy jacks with easy bag

### MOORING – ANCHORING

Self-bailing chain locker  
Dual stainless steel anchor roller at bow  
Vertical electrical windlass 12 Volt, 1600 Watt remote control  
(8) Aluminum mooring cleats, stainless steel deck chafe guards

### SAIL LOCKER

Access through deck hatch

### BOW CABIN – OPTIONAL

In lieu of the sail locker  
Access through deck hatch, stainless steel ladder, solid wood steps  
Cabin with single bed, foam mattress  
Toilet, sink with hot/cold water, shower

### DECK HARDWARE

Open stainless steel bow pulpit w/step  
Stainless steel aft pulpits  
(1) Ring lifebuoy bracket  
(1) Outboard engine bracket  
(1) Flag pole socket  
Double lifeline and stainless steel stanchions w/gates to port and to starboard

### COCKPIT

Self bailing cockpit  
Port and starboard lockers  
Gas locker for (2) bottles in cockpit  
Cockpit benches with wood inlays  
Dual steering wheel consoles w/leather covered stainless steel wheels (35")  
(1) Emergency tiller  
Dual compasses on console  
Engine control and panel to starboard  
Polyester cockpit table, (2) leaves, glove boxes, bottle storage, 12 Volt socket, lamp with shade  
(2) Waterproof stereo speakers

### SWIM PLATFORM

Access door to swim platform  
Natural solid wood decking on sun deck  
Liferaft locker  
Stainless steel swim ladder, solid wood steps  
Hot and cold transom shower  
(1) Shore power outlet

### ACCOMODATIONS

ALPI interior woodwork  
Parquet type laminated floors

### COMPANIONWAY

Headroom: 6; 9"  
Companionway with molded wood steps, non-slip surface  
(2) Leather covered stainless steel handrails

### FORWARD CABIN(S)

Version 1 Forward cabin  
Headroom: 6'5"  
Centerline "queen" bed w/marine mattress  
(1) Dressing table with mirror  
(2) Hull portholes with curtains  
(2) Opening deck hatches w/Ocean Air shade/screen  
Hanging lockers  
Shelves along hull  
Access to ensuite toilet

### FORWARD HEAD

Headroom: 6'4"  
Separate stall shower w/hot & cold water  
Manual marine toilet w/21 gal. holding tank  
Sink, synthetic resin countertop, hot & cold mixer tap  
Mirror, glass holder, soap tray, towel rail, trash bin, paper dispenser  
(1) Opening deck hatch w/Ocean Air shade/screen

### SALON

Headroom: 6'7"  
U-shaped salon bench, double density foam  
(2) Person settee with center foldaway armrest  
Storage under settees and along the hull  
(1) Panoramic window with pleated blinds  
(2) Hull portholes with curtains  
(2) Fixed salon windows with pleated blinds  
(1) Opening port in the starboard side window  
(3) Opening deck hatches w/Ocean Air shade/screens  
Cupboards and lockers

### CHART TABLE

Navigator's table w/hinged lid and storage  
Helmsman seat with cushion  
Pivoting electrical panel enabling access to electrical connections  
Navigation instrument panel (electronics optional)  
Radio CD player, stereo MP3, (2) speakers  
(1) Red/white lamp  
Leather covered stainless steel hand rail on bulkhead

### GALLEY

Headroom: 6'8"  
U-shaped galley fitted aft by companionway  
Synthetic resin countertop  
Double stainless steel sinks w/cutting board  
Gimballed 2 burner stove w/oven, safety bar  
Refrigerator 4.5 cubic foot, refrigeration unit 12 Volt, front opening  
3.5 cubic foot ice box top opening with 12 Volt refrigerating unit  
(1) Cutlery drawer  
Locker w/double door under sink & trash bin  
(1) Opening port

### STARBOARD AFT HEAD

Headroom: 6'9"  
Separate stall shower w/hot & cold water  
Manual marine toilet w/21 gal. holding tank  
Sink, synthetic resin countertop, hot & cold mixer tap  
Mirror, glass holder, soap tray, towel rail, trash bin, paper dispenser  
Fixed port w/privacy curtain  
(1) Opening port w/curtain

### AFT CABIN(S)

(2) Symmetrical cabins each consisting of:  
Headroom: 6'11"  
Double bed w/marine mattress  
Hanging locker  
(1) Fixed hull port w/curtain  
(2) Opening ports w/curtains  
(1) Opening deck hatch w/Ocean Air shade/screen

### ENGINE

Engine Yanmar diesel 4JH4HTE-110 hp  
Engine control, key ignition, control panel in cockpit  
Engine bed integrated in hull liner, soundproofed compartment w/insulating foam  
Alternator 12 Volt/80 Amp  
(1) Roto moulded diesel tank 125 gal (under starboard aft berth)  
Fixed three blade propeller  
(1) Engine access through companionway w/gas lifting piston, (2) engine access through aft cabins

### ELECTRICAL

12 Volt circuit, 110 Volt circuit  
(2) House batteries (2x140 Amp), (1) battery for engine (110 Amp)  
Battery charger 40 Amp, (1) shore power 110 Volt  
Electrical panel (12 Volt/110 Volt) circuit breakers, voltmeter, water gauge, fuel gauge, low battery warning, low fuel warning  
(1) 12 Volt outlet, (7) 110 Volt sockets  
Navigation lights, anchor light at masthead, deck light

### PLUMBING

(3) Rotomolded freshwater tanks (2 x 85 gal in the salon, 87 gal forward cabin)  
Pressurized electric water pump w/accumulator tank, filter  
Electric water heater 11 gal  
Electrical shower drain pumps  
(2) Electric bilge pumps, (1) manual bilge pump  
(1) Electric ice box drain pump

### GAS

(2) Gas bottle lockers in the cockpit (bottles optional)

### OPTIONS

Consult your dealer for all available options