



1 forward cabin - 1 Toilet, 2 AFT cabin - 2 Toilet, Bow cabin (optional extra)



2 forward cabins - 2 Toilets, 2 Aft cabins - 2 Toilet - Bow cabin (optional extra)

GENERAL SPECIFICATIONS

• L.O.A	59' 10"
• Length of hull	58' 3"
• L.W.L	53' 11"
• Width of hull	16' 4"
• Deep keel (min)	8' 6"
• Ballast	14,186 lbs
• Shoal keel (min)	6' 11"
• Ballast	15,763 lbs
• Mast height over water (max)	90' 3"
• Light displacement EC	47,747 lbs
• Fuel tank capacity (max)	285 gal
• Freshwater capacity (max)	269 gal
• Engine power	140 HP

ARCHITECTS / DESIGNERS

- Architect Naval : Berret Racoupeau
- Architecture interior : Nauta Design

EC CERTIFICATE

- Category A - 12 persons
- Category B - 13 persons
- Category C - 14 persons

SAIL LAYOUT AND AREA

• Mainsai	1001 sq ft
• Furling mainsail (optional extra)	797 sq ft
• Genoa	120 % 990 sq ft
• Asymmetric spi (optional extra)	2745 sq ft
• Staysail (optional extra)	376 sq ft
• I	78' 4"
• J	22' 7"
• P	75' 2"
• E	22' 8"

STANDARD EQUIPMENT

CONSTRUCTION

Design made following European Directive requirements and according to EC certification

- Monolithic hull design in polyester
- Monolithic structural counter moulding laminated and stuck to hull
- Deck in balsa and glass fibre sandwich covered in «diamond point» type non-slip surface
- Deck hull joint screwed, glued and banded with 1 solid wood bulwark, mechanically fastened
- Cast iron keel fixed with bolts and stainless steel nuts and glued
- Rudder foam core with glass compound stock and skin
- White coloured hull - Grey hull decoration

DECK EQUIPMENT

RIGGING

- Standard 9/10 anodized aluminum mast - stepped on keel - 3 Spreaders - MDS roller slides for mainsail
- Retractable steps on mast
- Boom in anodised aluminum
- Standing rigging in stainless steel
- Double backstay with turnbuckles
- Rigid boom vang with tackle
- Genoa furler manual - Drum on deck
- 2 mainsheet blocks on GRP arch
- 2 genoa sheet tracks with adjusted traveller cars - 2 Genoa sheet return blocks
- Complete running rigging: Main halyard, genoa halyard with clutch on mast and cleat, Boom topping lift with cleat on mast, Mainsail outhaul and sheet, 2 Genoa sheets 3 reef lines
- 2 rows continuous line reefing for main
- 11 sheet clutches
- 6 Cleats
- Pre-fitted for spinnaker (6 eye plates and clutches)
- Wind indicator Windex

WINCHES

- 2 Self-tailing genoa sheet winches (H70.2 STC)
- 2 Self tailing rigging winches (H46.2 STC)
- 2 winch handle(s) Speedgrip
- 2 Winch handle boxes

SAILS

- Double seamed Dacron furling genoa with UV protective coating
- Mainsail - Full batten Dacron double seamed
- Lazy-jacks - Silver Easy bag

MOORING - ANCHORING

- Self-bailing chain locker - with chain stopper
- Hatch giving access to chain locker in sail hold / Bow cabin
- Stainless steel bow fitting 2 rollers - Asymmetric spinnaker tack point
- Vertical electrical windlass 24 V -2000 W - Remote control
- 8 Stainless steel mooring cleats - Stainless steel dock line protection

SAIL LOCKER

- Access through deck hatch
- Stainless steel ladder - solid wood steps
- 2 Cubby hole lockers

DECK SECURITY

- 1 Open stainless steel forward pulpit with Step
- 2 stainless steel aft pushpits - 2 Stainless steel helmsman seat bases with seat and back rests
- 1 Ring lifebuoy bracket
- 1 Outboard engine bracket
- 1 Flag pole socket
- Double lifelines and stainless steel stanchions - Lifeline gate opening to port and to starboard
- 2 Stainless steel hand rails on deck
- 2 Stainless steel hand rails on fixed arch at cockpit outlet

COCKPIT

- Cockpit self bailing
- 2 Lockers under helm seating - Opened by gas cylinder
- 24V electric air pump, for dinghy
- 2 Rope lockers with Step in front of helm stations
- Cockpit benches decked in natural solid wood
- 2 Steering wheel consoles: Steering wheel Stainless steel - 1100 mm diameter - leather covered - Brake - Steering Gear on partition - metal cable transmission system - navigation instrument stand (optional instruments) - Steering compass on binacle - Glass holder in stainless steel - Stainless steel guard rail
- Silver PVC helmsman backrest
- Deck plate for access to tiller system - 1 Emergency tiller
- Engine control and control panel to starboard
- Solid wood cockpit table - 2 leaves - glove boxes - bottle holder - 12 V socket - lamp with shade with Switch
- 2 water-proof loudspeakers below fixed arch
- Lamps LED under fixed arch
- Folding companionway door and PMMA sliding companionway hatch - Electric locking system

SUN DECK AND UPPER STERN

- Open access protected by stainless steel rails - 2 doors in Stainless steel
- Natural solid wood decking
- 1 Liferaft locker on starboard side - Opened by gas cylinder
- 1 LPG Gas locker on port side - Opened by gas cylinder
- 2 Wet lockers at skirt bottom
- Additional integrated lifting system for dingy
- 1 Stainless steel swimming ladder - solid wood steps
- 1 Shower with hot water /cold water
- 1 110 V shore power inlet

FITTINGS

- Light stained Alpi Mahogany cabinetry
- Parquet type laminated floors
- Deckhead, saloon hull and bulkhead covered with premium PVC fabric ceiling material

COMPANIONWAY

- Height to deck beam: 6' 10"
- Wooden companionway with hung steps in moulded wood with non-slip surface
- Stainless steel stairway ramps - leather covered
- PMMA canopy - Wrinkled blinds

Version 1 forward cabin

FORWARD CABIN

- Height to deck beam: 6' 11"
- Central double bed (6' 9" x 4' x 5 6") - Slatted bed base - Marine mattress
- Night tables - Cubby hole lockers - Drawers - glove boxes - Lockers under the bed (Opened by gas cylinder)
- Wardrobe - Cupboard - Shoe cabinet
- 1 Dressing table with mirror - 1 Removable seat
- Mirror on entrance wall
- 2 Portholes on hull with curtains
- 3 Deck hatches with blinds / Mosquito screen

STARBOARD FORWARD WASHROOM-Single cabin

- Height to deck beam: 6' 7"
- Private washroom accessible from forward cabin
- Separate shower: Shower tray complete - shower mixer tap hot/cold water - Shower screen PMMA
- Manual marine toilet
- Washbasin - Synthetic solid surface counter - Mixing tap hot water/cold water
- 2 Mirrors
- Toilet accessories: Glass holder - soap tray - towel rail - Trash bin - Paper holder
- Cupboards - Cubby hole lockers
- 1 Opening deck hatch with blackout shades/Mosquito screen

Version 2 forward cabins

FORWARD CABINS

- 2 Symmetrical cabins
- Height to deck beam: 6' 9"
- Double bed (6' 9" x 4' 11") - Slatted bed base - Marine mattress
- Hanging locker - Cubby hole lockers - Drawer - glove boxes
- Mirror on entrance wall
- 1 Porthole on hull with curtain
- 1 Opening deck hatch with blackout shades/Mosquito screen

WASHROOMS FORWARD- Two cabin

- Symmetrical bathrooms
- Height to deck beam: 6' 7"
- Private bathrooms accessible from forward cabins
- Separate shower: Shower tray complete - shower mixer tap hot/cold water - Shower screen PMMA
- Manual marine toilet
- Washbasin - Synthetic solid surface counter - Mixing tap hot water/cold water
- Mirror
- Toilet accessories: Glass holder - soap tray - towel rail - Trash bin - Paper holder
- Cupboard - Cubby hole locker
- 1 Opening deck hatch with blackout shades/Mosquito screen

SALOON

- Height to deck beam: 6' 8"
- U shaped saloon bench - Fabric upholstery
- Retractable central seat - Fabric upholstery
- Swivel foldaway saloon table wood - Laquered table top and inlay - Integrated bar
- Sofa with armrests
- 4 Matching decorative cushions
- Cupboards - Cubby hole lockers and storage along the hull - Bars - Storage space under seats and sofa
- 1 Panoramic window with hatches blinds/Mosquito screen
- 2 Portholes on hull with curtains
- 2 fixed deckhouse side windows with pleated blinds
- 4 Opening portholes in fixed side windows

CHART TABLE TO STARBOARD

- Electrical console with access - glove boxes - Storage - Moulded wood beading
- Helmsman seat with cushion and backrest
- Hinged backlit electrical panel (to allow access to electrical connections)
- Navigation instrument panel (optional instruments)
- Radio CD player/Stereo MP3 - 2 Loud speakers
- 1 Oilskins locker - 3 draw cabinet

GALLEY TO PORT

- Height to deck beam: 6' 9"
- U-shaped kitchen
- Synthetic solid surface counters
- Rectangular stainless steel sink - Rectangular stainless steel drain - Cutting board in solid wood
- 1 Spray-hose mixer-tap cold / hot
- 1 Gas cooker 3 burners, Stainless steel oven on hinges - safety bar - stove exhaust fan
- 1 Refrigerator 31 cu ft, Refrigeration unit 24 V, 2 speed compressor, front opening
- 1 Ice box 2.8 cu ft, Refrigeration unit 24 V, freezer, top opening
- Drawers with slides and buffers, Cupboards, equipped lockers (shelves with fiddles, dish towel holder, bottle holder)
- Trash bin - Refuse chute access
- 1 Porthole opening with curtain

STARBOARD AFT CABIN

- Height to deck beam: 6' 3"
- 2 single beds, can be joined to make a double bed (6' 7" x 2' 10" + 6' 7" x 2 6") - Slat bedbases - Marine mattress
- Hanging locker - Cubby hole lockers - glove boxes
- 1 Dressing table with mirror
- Mirror on entrance wall
- 1 Porthole opening on cockpit with curtain
- 1 Porthole opening on side with curtain
- 1 Transom window with curtain
- 1 Porthole opening towards transom

STARBOARD AFT WASHROOM

- Height to deck beam: 6' 9"
- Private wash room accessible from starboard aft cabin
- Separate shower: Shower tray complete - shower mixer tap hot/cold water - Shower guard PMMA
- Manual marine toilet
- 1 Rigid sewage water tank 21 gal
- Washbasin - Synthetic solid surface counter - Mixing tap hot water/cold water
- Mirror
- Toilet accessories: Glass holder - soap tray - towel rail - Trash bin - Paper holder
- Cupboard - Cubby hole locker
- 2 Porthole(s) opening onto coaming with curtain

PORT AFT CABIN

- Height to deck beam: 6' 3"
- 1 Double bed (6' 9" x 4' 7" x 5) - Slatted bed base - Marine mattress
- Hanging locker - Cubby hole lockers - glove boxes
- Mirror on entrance wall
- 1 Porthole opening on cockpit with curtain
- 1 Porthole opening on side with curtain
- 1 Transomwindow with curtain
- 1 Porthole opening towards transom

PORT AFT WASHROOM

- Height to deck beam: 6' 9"
- Wash room accessible from the port aft cabin and from the saloon
- Separate shower: Shower tray complete - shower mixer tap hot/cold water - Shower screen PMMA
- Manual marine toilet
- 1 Rigid sewage water tank 21 gal
- Washbasin - Synthetic solid surface counter - Mixing tap hot water/cold water
- Mirror
- Toilet accessories: Glass holder - soap tray - towel rail - Trash bin - Paper holder
- Cupboards - Cubby hole locker
- 1 Porthole(s) opening onto coaming with curtain

ENGINE

- Engine 140 CV Volkswagen
- Engine electrical control and panel at the starboard helm
- Engine compartment: Foam soundproofing - Ventilation: 1 air intakes and 1 air outlets with exhaust fan
- 1 Alternator 12 V: 120 Amperes
- 1 Alternator 24 V: 80 Amperes
- 2 Rotation moulded diesel tanks (63 gal under aft berth to port + 63 gal under aft berth to starboard) - Electronic gauge - Low level alarm - 2 Deck fillers - Tank selection with 1/4 by-pass valves
- Filters: Sea water - Diesel - Decanter
- Stainless steel shaft
- 3 retractable blades propeller
- 1 Engine access through companionway (Opening by 2 gas bottles) - Engine access through passageway and aft cabins

ELECTRICITY

- 12 V circuit
- 24 V circuit
- 110 V circuit
- Ducts with messenger lines for threading cables of electrics or navigation electronics optional extras
- 1 Electrical panel 110 V: Breaker - Voltmeter
- 1 Electrical panel 12 V 24 V: Breaker - Voltmeter - Water gauge - Fuel gauge - Charging current and consumption current measurement 24 V
- Compartment to house the electrical equipment controls (Standard or Optional) in the port aft cabin

12 V circuit

- Standard equipment: Sockets 12V, Hifi
- Prefitting for Optional extra: Hifi, Electronics
- 1 Battery for engine 12 V - 110 Amperes
- 1 Service battery 12 V - 110 Amperes
- Battery switch (Port passageway)
- Charge divider 12 V
- 1 Battery charger 12 V: 25 Amperes
- 2 Socket(s) 12 V (Chart table x 1 - Cockpit table x 1)

24 V circuit

- Standard equipment: Electric windlass - Pumps - Navigation lights - Lighting - Refrigeration units
- Prefitting for Optional extra: Bow thruster
- 1 Service 12V battery set - 280 Amperes (4 Batteries 12 V - 140 Amperes)
- Battery switch (Port passageway)
- Charge divider 24 V
- 1 Battery charger 24 V: 60 Amperes

110 V circuit

- Standard equipment: Sockets 110 V - Water heater
- Prefitting for Optional extra: Electrical cooker - Microwave oven - Water maker - Ice maker - Air conditioning - Hood - Washing machine - Dishwasher
- Sockets 110 V:
 - Version 3 cabin: 21 Sockets (Forward cabin x 5 - Fore washroom x 1 - Port saloon x 2 - Galley x 2 - Chart table x 4 - Port aft cabin x 2 - Port aft washroom x 1 - Starboard aft cabin x 3 - Starboard aft washroom x 1)
 - Version 4 cabin: 19 Sockets (2 Forward cabins x 2 - Port saloon x 2 - Galley x 2 - Chart table x 4 - Port aft cabin x 3 - Starboard aft washroom x 1)

Lighting

- Interior lights LED:
 - Overhead lights, Indirect lighting, Adjustable wall-mounted luminaires and reading lamps
 - Courtesy lamps in wardrobes
- Outside lighting:
 - LED: Lamps under fixed arch
 - Incandescent: Deck searchlight at mid mast, Spotlights bars arrow, Shade lamp on cockpit table
- Navigation lights LED - Control on chart table and on starboard helm
 - 1 Anchor light at mast top
 - 1 Automatic steaming light at mid mast
 - 1 Port navigation light, 1 Starboard on bow pulpit
 - 1 Sternlight on pushpit to starboard



Beneteau Oceanis 58

Provisional General Equipment

PLUMBING

- 2 rotation moulded freshwater tanks (2 x 87 gal in square inner moulding) - 2 Deck fillers - Tank selection with ¼ by-pass valves
- Pressurised electric water pump - Expansion chamber - System protection filter
- Electric water heater 16 gal
- 2 Rigid sewage water tank 2 x 21 gal (Port and starboard aft toilets)
- Automatic electric shower drain pumps - time delay
- 2 Electric bilge pumps - 1 Manual bilge pump
- 1 Electric ice box drain pump

GAS

- Gas bottle(s) locker in port aft skirt
- Regulator and solenoid

TRIM LEVEL

	AVANTAGE	ELEGANCE
Electronics - TFT ST70 RAYMARINE (Loch - Speedometer - Depth sounder - Weather vane - Anomomter)	■	■
Releasable fore-stay chain-plate	■	■
Cockpit sole decked in natural solid wood	■	■
1 Port electric maneuvering winch H46.2 STCEH	■	■
Supplementary diesel tanks (2 x 79 gal in saloon)	■	■
Spare water tank (79 gal Under the bed Forward)	■	■
Saloon: Speakers BOSE ACOUSTIMASS® 3	■	■
Shore freshwater supply connection	■	■
Galley: Fresh water filter	■	■
Galley: Extractor hood	■	■
Galley: Electric pump - Sea water	■	■
Version 3 cabin: Electric toilet - in forward head	■	■
Version 4 cabin: Electric toilet - Aft toilet to starboard	■	■
24 V circuit: 2 service batteries (4 x 140 Amperes - 12 V) + Additional battery charger 60 amperes	■	■
Sea Pump for deck washing		■
Safe		■
Chart table: Universal recharging station (Mobile, Walkman, GPS, PDA, etc...)		■
Chart table: Drawer refrigerator - 3.1 cu ft - Refrigeration unit 24 V under seat		■
Leather-covered doors and glove compartment - 2 Glove boxes of the steering wheel		■
Salon side table		■
Inverter 2000 W - 24 V / 110 V		■
Electric lateral blinds		■
Powered entrance door - 2 Remote controls		■

OPTIONS

PACKS

PACK ELECTRONIC RAYMARINE

- Adjustable and swiveling tracer support on cockpit table
- Cockpit: Multifunction screen C140W colour 14" (GPS, tracker, Cartography Navionics Silver Europe included, Chart tracker, Without chart)
- Cockpit: Auto pilot ST70 - Piston LS 50 - Gyrocompass - Keyboard command
- Chart table: Multifunction screen C120W colour 12" (GPS, tracker, Cartography Navionics Silver Europe included, Chart tracker, Without chart)
- Chart table: PC interface

PACK EASY DOCKING

- Bow thruster
- Windlass control in cockpit with chain counter
- 2 Steering wheels covers Silver
- Fenders protective covers Black
- Mooring kit (Anchor in stainless steel Delta 40 kg - 100M of 12mm diameter chain) - 4 Mooring ropes - 8 Fenders

OTHER OPTIONS

Navigation electronics RAYMARINE

- Remote pilot control, Wireless instruments repeater Smartcontroller
- Radar (radome only)
- Receiver AIS
- VHF

Rigging - Sails

- Anodized furling mast with - Mylar Taffetas tri-radial cut mainsail and genoa
- Hydranet sails for classic mast: Hydranet tri-radial cut mainsail and genoa
- Hydranet flying staysail on furler and track self-tacking - Fixed stay-sail furler with Hydranet staysail
- Code 5 (light air gennaker)
- Asymmetric spinnaker rigging - Asymmetric spi
- Symmetrical spinnaker rigging - Boom
- 2 flag halyards
- Easy Sail (Genoa traveller adjustment from cockpit, Clutches on genoa sheet foot blocks, Hydraulic backstay at centre, Winch handle Harken Speedgrip additional, Emergency rope cutter)



Beneteau Oceanis 58

Provisional General Equipment

Winches

- Electrical maneuvering winch to starboard H46.2 STCEH
- 2 Electric genoa sheet winches H70.2 STCEH

Bow cabin

In place of the sail hold

- Access through deck hatch - Stainless steel ladder, solid wood steps
- Height to deck beam: 6' 4"
- 2 Bunk beds (Bottom bunk 6' 4" x 2' 2" - Folding upper bed 6' 4" x 2' 2") - Foam mattress - Cover PVC
- Hanging locker - Storage locker - Cupboard
- Manual toilet - Washbasin - Shower head mixer tap hot/cold water
- Shower tray

Hull - Deck

- Solid wood layed side decks
- Cradle - Instrument holder davit
- Gangway - Hydraulic crane
- Gangway ladders
- Silver deck house dodger
- Cockpit Bimini top Silver
- PVC cockpit cushions

Interior equipment

- Water maker 100 L/H
- Generator 9.5 KVA
- Gel batteries
- Hot water heat system
- Air conditioning
- Dishwasher 110V
- Washing machine 110V
- Ice maker 110V
- 12 person crockery set
- Electric toilet (additional)
- Additional rigid toilet holding tanks
- TV aerial
- Varnished wood cabin soles
- Optional fabrics, Amaretta Kx or leather following colour chart